



- Magnetic principle
- Excellent resistance to workshop conditions (DL310B: IP64).
Resistant to dust and vibrations.
- Compact size ideal for designing into machines.
- A/B phase output by open collector
- Measuring range: 10 mm / 0.39" and 30 mm / 1.18"




Digital Gauge

Dimensions

DL310B



DL330B



Unit: mm/inch

Specifications

Model	DL310B	DL330B
Measuring range	10 mm / 0.39"	30 mm / 1.18"
Resolution	10 µm	10 µm
Accuracy (at 20 °C / 68 °F)	± 5 µm	± 5 µm
Measuring force	1.5 N or less	1.5 N or less
Output signal	A/B phase by NPN open collector (12 VDC, 10 mA or less)	
Maximum response speed ^{*1}	120 m/min	—
Protective design grade	Equivalent to IP 64	—
Mounting stem diameter	ø 8 $\frac{+0.01}{-0.01}$ mm / ø 0.31 $\frac{+0.0004}{-0.0004}$ "	
Operating temperature	0 °C to 50 °C / 32 °F to 122 °F	
Storage temperature	-10 °C to 60 °C / 14 °F to 140 °F	
Power supply	5 VDC ± 5%	
Power consumption	0.2 W	
Cable length	2 m / 6.56 ^{+/-2}	
Feeler	Feeler tipped with 3 mm dia. carbide ball with M2.5 x 0.45 screw on fitting end (DZ123)	
Mass (excl. cable unit)	60 g / 2.12 oz	90 g / 3.17 oz
Vacuum pressure for Air lifter	6.0 x 10 ⁻⁴ to 7.5 x 10 ⁻⁴ Pa	—

*1: Max. response speed of the electrical circuit.

*2: Please consult our sales for more than 2m.

*Consult us when using DL310B/ 330B with the probe facing upward.

Diese Daten können jederzeit ohne Vorankündigung geändert werden

WayCon Positionsmesstechnik GmbH

e-mail: info@waycon.de

internet: www.waycon.de

Head Office

Mehlbeerstr. 4

82024 Taufkirchen

Tel. +49 (0)89 67 97 13-0

Fax +49 (0)89 67 97 13-250

Office Köln

Auf der Pehle 1

50321 Brühl

Tel. +49 (0)2232 56 79 44

Fax +49 (0)2232 56 79 45